

鋼板系

■ 鋼板

厚さ	単重 kg/m ²	幅×長さ		
		3'×6' 914× 1,829	4'×8' 1,219× 2,438	5'×10' 1,524× 3,048
1.6	12.56	●	●	●
2	15.70			
2.3	18.06	●	●	●
3.2	25.12	●	●	●
4.5	35.32	●	●	●
6	47.10	●	●	●
8	62.80			
9	70.65	●	●	●
10	78.50			
12	94.20	●	●	
14	109.9			
16	125.6			
19	149.2			

厚さ	単重 kg/m ²	幅×長さ		
		5'×20' 1,524× 6,096	7'×20' 2,134× 6,096	6'×5,500 1,829× 5,550
9	70.65		●	
10	78.50			
12	94.20		●	
14	109.9			
16	125.6		●	
19	149.2		●	
22	172.7		●	
25	196.2		●	
28	219.8		●	
30	235.5			
32	251.2		●	
36	282.6			●
38	298.3			
40	314.0			
42	329.7			
45	353.2			
50	392.5			

● SS400

■ ミガキ鋼板

厚さ	単重 kg/m ²	幅×長さ	
		3'×6' 914× 1,829	4'×8' 1,219× 2,438
0.4	3.140		—
0.5	3.925		—
0.6	4.710		—
0.8	6.280	●	
1	7.850	●	●
1.2	9.420	●	●
1.6	12.56	●	●
2	15.70	●	
2.3	18.06	●	●
2.6	20.41		
2.9	22.76		
3.2	25.12	●	

鋼板とミガキ鋼板の違い

ミガキ鋼板は、鋼板と違い、黒皮が取り除かれた状態で白銀色の滑らかな表面をしています。寸法精度は高いですが、黒皮がない分錆が発生しやすいです。

■ 縞鋼板

厚さ	単重 kg/m ²	幅×長さ			
		1m×3m 1,000× 3,000	3'×6' 914× 1,829	4'×8' 1,219× 2,438	5'×10' 1,524× 3,048
2.3	19.73		●		—
3.2	26.82		●	●	●
4.5	37.02		●	●	●
6	48.80		●	●	●
9	72.34		●	●	
12	95.87				

■ ボンド鋼板

厚さ	単重 kg/m ²	幅×長さ		
		3'×6' 914× 1,829	4'×8' 1,219× 2,438	5'×10' 1,524× 3,048
0.6	4.710		—	—
0.8	6.280			—
1	7.850			—
1.2	9.420			—
1.6	12.56	●	●	
2.3	18.06			
3.2	25.12			

■ 高張力鋼板 (55K鋼)

厚さ	単重 kg/m ²	幅×長さ	
		4'×8' 1,219× 2,438	5'×10' 1,524× 3,048
3.2	25.12		
4.5	35.32		
6	47.10	●	
9	70.65	●	
12	94.20	●	
16	125.6	○	
19	149.2		
22	172.7		
25	196.2		

■ エキスパンドメタル

単重 kg/枚

規格	厚さ	幅×長さ		
		3'×6' 914× 1,829	4'×8' 1,219× 2,438	5'×10' 1,524× 3,048
XG21	4.5	● 22.9	● 40.7	63.6
XG22	6	● 30.6	● 54.4	85.0
XS42	2.3	● 6.86	● 12.2	19.0
XS43	3.2	● 13.4	● 23.8	37.2

■ ステンレス (SUS304)

単重 kg/枚

厚さ	幅×長さ		
	1m×2m 1,000× 2,000	4'×8' 1,219× 2,438	5'×10' 1,524× 3,048
0.5	7.93	11.8	—
0.6	9.52	14.1	—
0.8	12.7	18.9	—
1	● 15.9	23.6	36.8
1.2	● 19.0	28.3	44.2
1.5	● 23.8	● 35.4	55.3
2	● 31.7	● 47.1	73.7
2.5	39.6	58.9	92.1
3	● 47.6	● 70.7	111
4	63.4	94.3	147
5	79.3	118	184
6	95.2	141	221

表面 2B

■ ピース

規格	
5032-S (60-1)	●
5032-D (60-2)	
6040-S (75-1)	●
6040-D (75-2)	
8053-S (100-1)	●
8053-D (100-2)	

目方向

(XS)スタンダードタイプ

(XG)グレーチングタイプ



ソロバン目

タタミ目

単位面積 m²/枚

幅×長さ

3'×6'	4'×8'	5'×10'
1.672	2.972	4.645

● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)

■平鋼

単重 kg/m

幅	長さ 5.5m									
	厚さ									
	3	4.5	6	9	12	16	19	22	25	
13	0.306	● 0.459	● 0.612	—	—	—	—	—	—	—
16	0.377	● 0.565	● 0.754	● 1.13	—	—	—	—	—	—
19	0.447	● 0.671	● 0.895	● 1.34	—	—	—	—	—	—
22	0.518	● 0.777	● 1.04	● 1.55	2.07	—	—	—	—	—
25	● 0.589	● 0.883	● 1.18	● 1.77	● 2.36	3.14	3.73	—	—	—
32	● 0.754	● 1.13	● 1.51	● 2.26	● 3.01	4.02	4.77	5.53	6.28	—
38	● 0.895	● 1.34	● 1.79	● 2.68	● 3.58	4.77	5.67	6.56	7.46	—
44	1.04	● 1.55	● 2.07	● 3.11	● 4.14	5.53	6.56	7.60	8.64	—
50	● 1.18	● 1.77	● 2.36	● 3.53	● 4.71	6.28	7.46	8.64	9.81	—
65	○ 1.53	● 2.30	● 3.06	● 4.59	● 6.12	8.16	9.69	11.2	12.8	—
75	1.77	● 2.65	● 3.53	● 5.30	● 7.06	9.42	11.2	13.0	14.7	—
90	2.12	3.18	● 4.24	● 6.36	● 8.48	11.3	13.4	15.5	17.7	—
100	2.36	● 3.53	● 4.71	● 7.06	● 9.42	12.6	14.9	17.3	19.6	—
125	2.94	4.42	5.89	● 8.83	● 11.8	15.7	18.6	21.6	24.5	—
150	3.53	5.30	7.06	● 10.6	● 14.1	18.8	22.4	25.9	29.4	—


幅	長さ 6.0m								
	厚さ								
	6	9	12	16	19	22	25	28	32
60	2.83	4.24	5.65	7.54	8.95	10.4	—	—	—
70	3.30	● 4.95	6.59	8.79	10.4	—	—	—	—
80	3.77	● 5.65	7.54	10.0	11.9	—	—	—	—
110	5.18	7.77	10.4	13.8	16.4	19.0	21.6	—	—
165	7.77	11.7	15.5	—	—	—	—	—	—
175	8.24	12.4	16.5	—	—	—	—	—	—
180	8.48	12.7	17.0	22.6	26.8	—	—	—	—
200	9.42	● 14.1	● 18.8	25.1	29.8	34.5	39.2	44.0	50.2
250	11.8	● 17.7	● 23.6	31.4	37.3	43.2	49.1	—	62.8
300	14.1	● 21.2	● 28.3	37.7	44.7	51.8	58.9	—	—
350	—	24.7	33.0	44.0	52.2	—	—	—	—
400	—	—	37.7	50.2	—	—	—	—	—

● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)

H形鋼 / C形鋼


■ H形鋼

寸法				単重 kg/m	長さ						
H × B	t1	t2	6m		7m	8m	9m	10m	11m	12m	
100 × 100	6	8	16.9		●	●	●	●			
125 × 125	6.5	9	23.6		●	●	●	●			
150 × 150	7	10	31.1		●	●	●	●			
175 × 175	7.5	11	40.4								
200 × 200	8	12	49.9								
250 × 250	9	14	71.8								
300 × 300	10	15	93.0								
350 × 350	12	19	135	—							
400 × 400	13	21	172	—							
150 × 75	5	7	14.0		●	●	●	●			
175 × 90	5	8	18.0		●	●	●	●			
200 × 100	5.5	8	20.9		●	●	●	●			
250 × 125	6	9	29.0		●	●	●	●			
300 × 150	6.5	9	36.7		●	●	●	●			
350 × 175	7	11	49.4	—							
400 × 200	8	13	65.4	—							



■ C形鋼

寸法				単重 kg/m	長さ						
T × H × A × C	6m	7m	8m		9m	10m	11m	12m			
1.6 × 60 × 30 × 10	●	—	●	—	—	—	—	—			
2.3 ×	●	—	●	—	—	—	—	—			
1.6 × 75 × 45 × 15	2.32	—	●	—	—	—	—	—			
2.3 ×	3.25	●	●	●	●	—	—	—			
1.6 × 100 × 50 × 20	2.88	—	●	—	—	—	—	—			
2.3 ×	4.06	●	●	●	●	—	—	—			
3.2 ×	5.50	●	●	—	—	—	—	—			
2.3 × 120 × 60 × 20	4.78	—	—	—	—	—	—	—			
3.2 ×	6.51	—	—	—	—	—	—	—			
2.3 × 125 × 50 × 20	4.51	—	—	—	—	—	—	—			
3.2 ×	6.13	—	—	—	—	—	—	—			
3.2 × 150 × 50 × 20	6.76	—	—	—	—	—	—	—			
3.2 × 150 × 65 × 20	7.51	—	—	—	—	—	—	—			
3.2 × 150 × 75 × 25	8.27	—	—	—	—	—	—	—			
3.2 × 200 × 75 × 20	9.27	—	—	—	—	—	—	—			




● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)

チャンネル

■チャンネル

寸法				単重 kg/m	長さ		
t1	× B	× H	t1		t2	5.5m	メッキ 5.5m
5	× 40	× 75	5	7	6.92	●	
5	× 50	× 100	5	7.5	9.36	●	●
6	× 65	× 125	6	8	13.4	●	
6.5	× 75	× 150	6.5	10	18.6	●	
9	×		9	12.5	24.0	●	
7	× 75	× 180	7	10.5	21.4		
7.5	× 80	× 200	7.5	11	24.6	●	
8	× 90	× 200	8	13.5	30.3	●	
9	× 90	× 250	9	13	34.6		
11	×		11	14.5	40.2		
9	× 90	× 300	9	13	38.1		
10	×		10	15.5	43.8		
12	×		12	16	48.6		
10.5	× 100	× 380	10.5	16	54.5		
13	×		6.5	20	67.3		





アングル

■アングル

寸法	単重 kg/m	長さ		
		5.5m	カラー 6m	メッキ 5.5m
t × A × B				
3 × 20 × 20	0.885	●		
3 × 25 × 25	1.12	●		
3 × 30 × 30	1.36	●	●	
5 ×	2.16	●		
3 × 40 × 40	1.83	●	●	
5 ×	2.95	●		
4 × 45 × 45	2.74			
4 × 50 × 50	3.06	●	●	●
6 ×	4.43	●	●	●
8 ×	5.78			
6 × 65 × 65	5.91	●	●	
8 ×	7.66	●		
6 × 75 × 75	6.85	●	●	
9 ×	9.96	●		
12 ×	13.0			
7 × 90 × 90	9.59	●		
10 ×	13.3	●		
13 ×	17.0			
7 × 100 × 100	10.7	●		
10 ×	14.9	●		
13 ×	19.1			
9 × 130 × 130	17.9			
12 ×	23.4			
15 ×	28.8			
12 × 150 × 150	27.3			
15 ×	33.6			

■不等辺アングル

寸法	単重 kg/m	長さ 5.5m
t × A × B		
9 × 75 × 90	11.0	
7 × 75 × 100	9.32	●
10 ×	13.0	
13 ×	16.5	
7 × 75 × 125	10.7	●
10 ×	14.9	
13 ×	19.1	
9 × 90 × 125	14.6	
10 ×	16.1	
13 ×	20.6	
9 × 90 × 150	16.4	
12 ×	21.5	
15 ×	26.5	
9 × 100 × 150	17.1	
12 ×	22.4	
15 ×	27.7	



● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)



丸鋼 / 角鋼 / 異形丸鋼

■ 丸鋼

径 D	単重 kg/m	長さ	
		5.5m	6.0m
6	0.222	●	
9	0.499	●	
13	1.04	●	
16	1.58	●	
19	2.23	●	
22	2.98	●	○
25	3.85	●	
28	4.83		
32	6.31		
36	7.99		
38	8.90		
42	10.9		
44	11.9		
48	14.2		
50	15.4		
55	18.7		
60	22.2		
65	26.0		
70	30.2		

■ 角鋼

辺長 A	単重 kg/m	長さ 5.5m
9.5	0.712	●
12.7	1.27	●
16	2.01	●
19	2.83	●
22	3.80	●
25	4.91	●
28	6.15	
32	8.04	●
38	11.3	●
44	15.2	●
50	19.6	●
65	33.2	
75	44.2	
90	63.6	
100	78.5	




● SR235

■ 異形丸鋼

呼称	公称直径 D	単重 kg/m	長さ								
			4.0m	4.5m	5.0m	5.5m	6.0m	6.5m	7.0m	7.5m	8.0m
D10	9.53	0.560			●	●■	●				
D13	12.7	0.995			●	●■	●				
D16	15.9	1.56				●■	●				
D19	19.1	2.25						■			
D22	22.2	3.04									
D25	25.4	3.98									
D29	28.6	5.04									
D32	31.8	6.23									
D35	34.9	7.51									
D38	38.1	8.95									
D41	41.3	10.5									
D51	50.8	15.9									

● SD295 ■ SD345




● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)

角パイプ

■角パイプ (STKMR)

寸法 t × A × B	単重 kg/m	長さ 5.5m	ライト キャップ
* 1.6 × 13 × 13	0.690	●	
* 1.2 × 14 × 14	0.530		○
* 1.2 × 16 × 16	0.621		
* 1.6 ×	0.813	●	○
* 1.2 × 19 × 19	0.716		
* 1.6 ×	0.939	●	○
* 1.2 × 21 × 21	0.811		
* 1.6 ×	1.07	●	○
* 1.2 × 24 × 24	0.906		
* 1.6 ×	1.19		
* 1.2 × 25 × 25	0.971		
* 1.6 ×	1.28	●	○
* 1.2 × 28 × 28	1.09		
* 1.6 ×	1.44		
* 1.2 × 32 × 32	1.23		
* 1.6 ×	1.62		
* 1.6 × 38 × 38	1.94		
* 1.6 × 45 × 45	2.32		
* 1.2 × 22 × 10	0.621	●	○
* 1.2 × 25 × 12	0.716		
* 1.6 ×	0.939	●	
* 1.2 × 32 × 14	0.906		
* 1.6 ×	1.19	●	
* 1.2 × 28 × 18	0.906		
* 1.6 ×	1.19		
* 1.2 × 40 × 16	1.09		
* 1.6 ×	1.44		
* 1.2 × 40 × 25	1.23		
* 1.6 ×	1.62	●	○
* 1.6 × 50 × 26	1.94	●	○
* 1.6 × 60 × 30	2.32	※STKR	
* 1.6 × 70 × 25	2.44		
* 1.6 × 84 × 32	2.94		
1.2 × 26 × 26	0.906		
1.6 ×	1.19		
1.2 × 31 × 31	1.09		
1.6 ×	1.44	●	●
1.6 × 40 × 40	1.94	●	●
1.2 × 30 × 20	0.906		
1.6 ×	1.19	●	○
1.2 × 40 × 20	1.09		
1.6 ×	1.44	●	○
1.6 × 50 × 30	1.94	●	○
1.6 × 60 × 35	2.32		
1.6 × 70 × 25	2.44		
1.6 × 70 × 30	2.44		
1.6 × 80 × 40	2.94		
1.6 × 90 × 30	2.94		

* 角出し



■角パイプ (STKR)


寸法 t × A × B	単重 kg/m	長さ					ライト キャップ
		6m	8m	カラー			
				6m	8m	10m	
2.3 × 30 × 30	2.03	●					
2.0 × 40 × 40	2.41						
2.3 ×	2.62	●					
3.2 ×	3.58						
1.6 × 50 × 50	2.38	●					●
2.3 ×	3.34	●		●			
3.2 ×	4.50	●					
4.5 ×	6.02						
6.0 ×	7.56						
1.6 × 60 × 60	2.88	●					●
2.3 ×	4.06	●		●			
3.2 ×	5.50	●					
4.5 ×	7.43						
2.3 × 75 × 75	5.14	●		●	●		●
3.2 ×	7.01	●					
4.5 ×	9.55						
6.0 ×	12.3						
2.3 × 100 × 100	6.95	●	●	●	●	●	●
3.2 ×	9.52	●	●	●	●	●	
4.5 ×	13.1	●	●				
6.0 ×	17.0						
3.2 × 125 × 125	12.0	●					
4.5 ×	16.6						
6.0 ×	21.7						
4.5 × 150 × 150	20.1		●				
6.0 ×	26.4						
6.0 × 175 × 175	31.1		●				
2.3 × 40 × 20	2.03	●					
2.3 × 50 × 30	2.62	●					
1.6 × 60 × 30	2.13	●					○
2.3 ×	2.98	●		●			
3.2 ×	3.99	●					
2.3 × 75 × 45	4.06	●		●			○
3.2 ×	5.50	●					
4.5 ×	7.43						
2.3 × 80 × 40	4.20		●				
3.2 ×	5.77						
2.3 × 100 × 50	5.14	●		●	●		○
3.2 ×	7.01	●					
4.5 ×	9.55						
6.0 ×	12.3						
2.3 × 125 × 75	6.95						
3.2 ×	9.52						
4.5 ×	13.1						
6.0 ×	17.0						
3.2 × 150 × 100	12.0						
4.5 ×	16.6						
6.0 ×	21.7		●				
4.5 × 200 × 100	20.1						
6.0 ×	26.4						

● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)

コラム

■コラム (BCR)

寸法		単重 kg/m	長さ 8m	対応 裏当て
A × B	t			
200 × 200	6	35.6	●	
	8	46.5		
	9	51.8	○	
	12	67.0		●
250 × 250	6	45.0		
	9	65.9	○	
	12	85.8	○	
300 × 300	6	54.4		
	9	80.1		
	12	105		
	16	136		
350 × 350	9	94.2		
	12	123		
	16	161		
400 × 400	9	108		
	12	142		
	16	186		
	19	218		



丸パイプ

■丸パイプ (STK)


寸法		単重 kg/m	長さ 5.5m
φ	t		
21.7	1.9	0.928	●
27.2		1.19	●
21.7	2.3	1.10	
27.2		1.41	●
34		1.80	●
42.7		2.29	●
48.6		2.63	●
60.5		3.30	●
60.5		3.98	
76.3	2.8	5.08	●

■丸パイプ (STKM)

寸法		単重 kg/m	長さ 5.5m
φ	t		
15.9	1.2	0.435	
	1.6	0.564	●
	2	0.686	
19.1	1	0.446	
	1.2	0.530	
	1.6	0.690	●
	2	0.843	
22.2	1.2	0.621	
	1.6	0.813	
	2	0.996	
25.4	1.2	0.716	
	1.6	0.939	●
	2	1.15	
	2.3	1.31	
	3.2	1.75	
28.6	1.2	0.811	
	1.6	1.07	
	2	1.31	
31.8	1.2	0.906	
	1.6	1.19	●
	2	1.47	
	2.3	1.67	

■丸パイプ (SGP)

JIS呼称		寸法		単重 kg/m	長さ 5.5m
		φ	t		
6A	1/8B	10.5	2	0.419	●
8A	1/4B	13.8	2.3	0.652	●
10A	3/8B	17.3		0.851	●
15A	1/2B	21.7	2.8	1.31	●
20A	3/4B	27.2		1.68	●
25A	1B	34	3.2	2.43	●
32A	1 1/4B	42.7	3.5	3.38	●
40A	1 1/2B	48.6		3.89	●
50A	2B	60.5	3.8	5.31	●
65A	2 1/2B	76.3		7.47	●
80A	3B	89.1	4.2	8.79	●
90A	3 1/2B	101.6		10.1	●
100A	4B	114.3	4.5	12.2	●
125A	5B	139.8		15.0	●
150A	6B	165.2	5	19.8	●
175A	7B	190.7	5.3	24.2	●
200A	8B	216.3	5.8	30.1	●
225A	9B	241.8	6.2	36.0	
250A	10B	267.4	6.6	42.4	
300A	12B	318.5	6.9	53.0	
350A	14B	355.6		67.7	
400A	16B	406.4	7.9	77.6	



● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)

■ アンカーピン

寸法		
φ9 × 200 × 30		●
φ9 × 400 × 30		
φ13 × 600 × 35		
φ16 × 400 × 40		●

■ 異形ストレートピン

寸法		
D10 × 400		● ■
D13 × 500		● ■
D16 × 750		● ■
D16 × 1,000		●
D19 × 800		■
D19 × 1,000		■

■ SD345

■ 異形アンカーピン

寸法		
D10 × 200 × 35		●
D10 × 350 × 30		●
D10 × 400 × 35		●
D13 × 600 × 35		

■ クリンプ金網

寸法		
200 × 1,000		●
300 × 1,000		●

規格 φ2.3/25×15目

材質 亜鉛メッキ

■ 菱形金網

寸法		
2m × 5m		
2m × 10m		●

規格 φ2.0/50×50目

材質 亜鉛メッキ

■ フレーム (FCタイプ)

寸法		
FC-200 L=1,000		●
FC-200 L=1,300		●

材質 亜鉛メッキ

■ ワイヤーマッシュ

線径	寸法		幅×長さ 1m×2m
	網目		
φ2.6	50		
	100		
φ3.2	50		
	100		
	150		
φ5.0	50		
	100		
	150		
φ6.0	50		
	100		
	150		

材質 鉄

■ フィットスペーサー

品番	
F-30	
F-40	
F-50	●
F-60	
F-70	●
F-80	●
F-100	●
F-150	
F-200	

■ 結束線 (Uタイプ)

品番	
#21 × 300 (U-300)	
#21 × 350 (U-350)	●
#21 × 400 (U-400)	●
#21 × 450 (U-450)	●
#21 × 500 (U-500)	
#21 × 550 (U-550)	
#21 × 600 (U-600)	
#21 × 650 (U-650)	

規格 φ0.8

材質 亜鉛メッキ