

鋼板系

■ 鋼板

厚さ	幅×長さ		
	3'×6'	4'×8'	5'×10'
	914× 1,829	1,219× 2,438	1,524× 3,048
1.6	●	●	●
2			
2.3	●	●	●
3.2	●	●	●
4.5	●	●	●
6	●	●	●
8			
9	●	●	●
10			
12	●	●	
14			
16			
19			

厚さ	幅×長さ		
	5'×20'	7'×20'	6'×5,550
	1,524× 6,096	2,134× 6,096	1,829× 5,550
9		■	
10			
12		■	
14			
16		■	
19		■	
22		■	
25		■	
28		■	
30			
32		■	
36			■
38			
40			
42			
45			
50			

■ : SS400

■ ミガキ鋼板

厚さ	幅×長さ	
	3'×6'	4'×8'
	914× 1,829	1,219× 2,438
0.4		—
0.5		—
0.6		—
0.8	●	
1	●	●
1.2	●	●
1.6	●	●
2	●	
2.3	●	●
2.6		
2.9		
3.2	●	

鋼板とミガキ鋼板の違い

ミガキ鋼板は、鋼板と違い、黒皮が取り除かれた状態で白銀色の滑らかな表面をしています。寸法精度は高いですが、黒皮がない分酸化しやすいです。

■ 縞鋼板

厚さ	幅×長さ			
	1,000× 3,000	3'×6'	4'×8'	5'×10'
		914× 1,829	1,219× 2,438	1,524× 3,048
2.3		●		—
3.2		●	●	●
4.5		●	●	●
6		●	●	●
9		●	●	
12				

■ ボンデ鋼板

厚さ	幅×長さ		
	3'×6'	4'×8'	5'×10'
	914× 1,829	1,219× 2,438	1,524× 3,048
0.6		—	—
0.8			—
1			—
1.2			—
1.6	●	●	
2.3			
3.2			

■ 高張力鋼板 (55K鋼)

厚さ	幅×長さ	
	4'×8'	5'×10'
	1,219× 2,438	1,524× 3,048
3.2		
4.5		
6	●	
9	●	
12	●	
16	○	
19		
22		
25		

■ エキスパンドメタル

規格	厚さ	幅×長さ		
		3'×6'	4'×8'	5'×10'
		914× 1,829	1,219× 2,438	1,524× 3,048
XG21	4.5	●	●	
XG22	6	●	●	
XS42	2.3	●	●	
XS43	3.2	●	●	

目方向

スタンダードタイプ
(ソロバン目)



グレーチングタイプ
(タタミ目)



■ ステンレス (SUS304)

厚さ	幅×長さ		
	1,000× 2,000	4'×8'	5'×10'
		1,219× 2,438	1,524× 3,048
0.5			—
0.6			—
0.8			—
1	●		
1.2	●		
1.5	●	●	
2	●	●	
2.5			
3	●	●	
4			
5			
6			

● : 2B

● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)