

鋼板系

■ 鋼板

厚さ	単重 kg/m ²	幅×長さ		
		3'×6'	4'×8'	5'×10'
		914× 1,829	1,219× 2,438	1,524× 3,048
1.6	12.56	●	●	●
2	15.70			
2.3	18.06	●	●	●
3.2	25.12	●	●	●
4.5	35.32	●	●	●
6	47.10	●	●	●
8	62.80			
9	70.65	●	●	●
10	78.50			
12	94.20	●	●	
14	109.9			
16	125.6			
19	149.2			

厚さ	単重 kg/m ²	幅×長さ		
		5'×20'	7'×20'	6'×5,500
		1,524× 6,096	2,134× 6,096	1,829× 5,550
9	70.65		●	
10	78.50			
12	94.20		●	
14	109.9			
16	125.6		●	
19	149.2		●	
22	172.7		●	
25	196.2		●	
28	219.8		●	
30	235.5			
32	251.2		●	
36	282.6			●
38	298.3			
40	314.0			
42	329.7			
45	353.2			
50	392.5			

● SS400

■ ミガキ鋼板

厚さ	単重 kg/m ²	幅×長さ	
		3'×6'	4'×8'
		914× 1,829	1,219× 2,438
0.4	3.140		—
0.5	3.925		—
0.6	4.710		—
0.8	6.280	●	
1	7.850	●	●
1.2	9.420	●	●
1.6	12.56	●	●
2	15.70	●	
2.3	18.06	●	●
2.6	20.41		
2.9	22.76		
3.2	25.12	●	

鋼板とミガキ鋼板の違い

ミガキ鋼板は、鋼板と違い、黒皮が取り除かれた状態で白銀色の滑らかな表面をしています。
寸法精度は高いですが、黒皮がない分酸化しやすいです。

■ 縞鋼板

厚さ	単重 kg/m ²	幅×長さ			
		1m×3m	3'×6'	4'×8'	5'×10'
		1,000× 3,000	914× 1,829	1,219× 2,438	1,524× 3,048
2.3	19.73		●		—
3.2	26.82		●	●	●
4.5	37.02		●	●	●
6	48.80		●	●	●
9	72.34		●	●	
12	95.87				

■ ボンデ鋼板

厚さ	単重 kg/m ²	幅×長さ		
		3'×6'	4'×8'	5'×10'
		914× 1,829	1,219× 2,438	1,524× 3,048
0.6	4.710		—	—
0.8	6.280			—
1	7.850			—
1.2	9.420			—
1.6	12.56	●	●	
2.3	18.06			
3.2	25.12			

■ 高張力鋼板 (55K鋼)

厚さ	単重 kg/m ²	幅×長さ	
		4'×8'	5'×10'
		1,219× 2,438	1,524× 3,048
3.2	25.12		
4.5	35.32		
6	47.10	●	
9	70.65	●	
12	94.20	●	
16	125.6	○	
19	149.2		
22	172.7		
25	196.2		

■ エキスパンドメタル

単重 kg/枚

規格	厚さ	幅×長さ		
		3'×6'	4'×8'	5'×10'
		914× 1,829	1,219× 2,438	1,524× 3,048
XG21	4.5	● 22.9	● 40.7	63.6
XG22	6	● 30.6	● 54.4	85.0
XS42	2.3	● 6.86	● 12.2	19.0
XS43	3.2	● 13.4	● 23.8	37.2

■ ステンレス (SUS304)

単重 kg/枚

厚さ	幅×長さ		
	1m×2m	4'×8'	5'×10'
	1,000× 2,000	1,219× 2,438	1,524× 3,048
0.5	7.93	11.8	—
0.6	9.52	14.1	—
0.8	12.7	18.9	—
1	● 15.9	23.6	36.8
1.2	● 19.0	28.3	44.2
1.5	● 23.8	● 35.4	55.3
2	● 31.7	● 47.1	73.7
2.5	39.6	58.9	92.1
3	● 47.6	● 70.7	111
4	63.4	94.3	147
5	79.3	118	184
6	95.2	141	221

表面 2B

■ ピース

規格	
5032-S (60-1)	●
5032-D (60-2)	
6040-S (75-1)	●
6040-D (75-2)	
8053-S (100-1)	●
8053-D (100-2)	

目方向

(XS)スタンダードタイプ

(XG)グレーチングタイプ



ソロバン目



タタミ目

単位面積 m²/枚

幅×長さ

3'×6'	4'×8'	5'×10'
1.672	2.972	4.645

● : 本社在庫 ● : 玉穂工場在庫
○ : 在庫成行 (要問い合わせ)